

## Modular Installation System, Room Control Box

### Room Control Box

#### Modules

##### RS 525/23



##### Universal Dimmer, 1 x AC 230 V, 10...250 VA, (R,L,C load)

- Rated operational voltage AC 230 V
- Rated power at +35°C ambient temperature: 10...250 VA
- Screw-less terminals for connection and through-wiring of untreated single-core, stranded or multi-core conductors, 0.5 ... 2.5 mm<sup>2</sup>
- With bus connection module
- Modular installation device for mounting in AP 118 automation module box or AP 641 room control box

The AP 641 room control box and AP 118 automation module box must be ordered separately.  
See Chapter Quick-assembly system - Room control box.

	Stock No.	Product No.	LK
	5WG1525-2AB23	<b>RS 525/23</b>	A

##### JB 525C23



##### Universal Dimmer, 1 x AC 120 V, 125 VA

- Rated operational voltage 120 V AC
- Rated power at +35°C ambient temperature: 10...125 VA
- Selectable mode for each output (normal mode, one- or two-level timer mode, blinking)
- As built-in device with 1/2 inch thread connection for mounting to or in a UL/NEMA Junction Box with feedthrough of the function wires through the 1/2 inch threaded connector

	Stock No.	Product No.	LK
	5WG1525-4CB23	<b>JB 525C23</b>	X

10