

ACVATIX™

2-port and 3-port valves, externally threaded, PN16

VVG44..., VXG44..




In small and medium-sized heating, ventilating and air conditioning systems as a control valve for mixing and diverting functions or as a shutoff valve. For closed circuits only.

- Housing made of bronze CC499K
- DN 15...40
- k_{vs} 0.25...25 m³/h
- Flat sealing, externally threaded connections G..B, as per ISO 228-1
- Siemens can deliver fitting sets ALG.. with threaded connection and ALS.. with welded connection
- Manual adjustment by means of mounted knob
- Can be equipped with motorized SAS.. actuators

Design

Valve cross-section:

VVG44..




Guided parabolic plug, integrated in the valve stem.

The seat is pressed to the valve body with the aid of special gland material.

Caution: The 2-port seat valve does not become a three-port valve by removing the cover plate!

VXG44..




Guided parabolic plug (as of DN25) which is integrated in the valve stem.

The seat is fitted in the through-port and attached directly to the valve body in the bypass.

From DN25, the seat in the through-port is attached directly to the valve body and fitted to the ring in the bypass.

Sizing

Flow diagram:



Δp_{max} = Maximum permissible differential pressure across the valve
(VXG44...: mixing port: Ports A-AB, B-AB, diverting: Ports AB-A, AB-B),
valid for the entire actuating range valve-actuator unit


Δp_{v100} = Differential pressure across the fully open valve and the valve's control path
(VXG44...: A - AB, B - AB) at a volume flow $\dot{V}_{100}$

$\dot{V}_{100}$ = Volume flow through the fully open valve (H_{100})

100 kPa = 1 bar $\approx$ 10 mWS


1 m³/h = 0.278 l/s water at 20 °C

Valve flow characteristic



Cavitation

Cavitation increases wear and tear on the parabolic plug and seat and results in unwanted noise. Cavitation can be prevented by not exceeding the differential pressures as per the flow diagram and maintaining the static pressures depicted below.




$\Delta p_{\max}$ = Differential pressure at a nearly closed valve to largely avoid cavitation

p_1 = Static pressure and the valve inlet

p_3 = Static pressure and the valve outlet

M Pump

J Water temperature



Example with hot water:

Pressure p_1 at valve inlet: 500 kPa (5 bar)

Water temperature: 120 °C


The above diagram clearly indicates that the maximum permissible differential pressure is $\Delta p_{\max} \rightarrow 200$ kPa (2 bar) at a nearly closed valve.

Note on chilled water applications

To prevent cavitation in chilled water circuits, sufficient counter pressure must be supplied to the valve output, e.g. using an additional butterfly valve downstream of the valve. Maximum permissible differential pressure over the valve: See 80 °C curve in the above diagram.

Operating pressure and operating temperature

Liquids:



Operating pressure and medium temperature per ISO 7005

(Observe all local and applicable laws).

Type summary

Type	DN	k_{vs}	S_v
		[m ³ /h]	
VVG44.15-0.25 VXG44.15-0.25	15	0.25	>50
VVG44.15-0.4 VXG44.15-0.4		0.4	
VVG44.15-0.63 VXG44.15-0.63		0.63	
VVG44.15-1 VXG44.15-1		1	
VVG44.15-1.6 VXG44.15-1.6		1.6	>100
VVG44.15-2.5 VXG44.15-2.5		2.5	
VVG44.15-4 VXG44.15-4		4	
VVG44.20-6.3 VXG44.20-6.3	20	6.3	
VVG44.25-10 VXG44.25-10	25	10	>100
VVG44.32-16 VXG44.32-16	32	16	
VVG44.40-25 VXG44.40-25	40	25	

DN = Nominal size

k_{vs} = Flow nominal value for cold water (5...30 °C) through a fully opened valve (H100), at a differential pressure of 100 kPa (1 bar)

S_v = Rangeability k_{vs} / k_{vr}

k_{vr} = Smallest k_v value at which the characteristic curve tolerance is still maintained, at a differential pressure of 100 kPa (1 bar)

Fittings

Type	Stock number	Description
ALG..2	BPZ:ALG..2	2 piece fittings set for 2-port valves, existing of 2 cap nuts, 2 insert nuts, and 2 flat seals. ALG..2B are fittings made of brass for media temperatures up to 100 °C
ALG..2B	S55846-Z1..	
ALG..3	BPZ:ALG..3	3 piece fittings set for 3-port valves, existing of 3 cap nuts, 3 insert nuts, and 3 flat seals. ALG..3B are fittings made of brass for media temperatures up to 100 °C
ALG..3B	S55846-Z1..	
ALS..2	BPZ:ALS..	2 piece on pipe fittings set with welded connection for 2-port valves, existing of 2 cap nuts, 2 insert nuts, and 2 flat seals

Equipment combinations

Valves	SAS.. actuators	
	Dp_{max}	Dp_s
	[kPa]	[kPa]
VVG44.15-0.25	400	1600
VVG44.15-0.4		
VVG44.15-0.63		
VVG44.15-1		725
VVG44.15-1.6		
VVG44.15-2.5		400
VVG44.15-4		
VVG44.20-6.3		750
VVG44.25-10		400
VVG44.32-16	250	250
VVG44.40-25	125	125

Valves	SAS.. actuators	
	Dp_{max} Mixing	Dp_{max} Diverting ¹⁾
	[kPa]	[kPa]
VXG44.15-0.25	400	100
VXG44.15-0.4		
VXG44.15-0.63		
VXG44.15-1		
VXG44.15-1.6		
VXG44.15-2.5		
VXG44.15-4		
VXG44.20-6.3		
VXG44.25-10		
VXG44.32-16	250	50
VXG44.40-25	125	35

¹⁾ Three-port valves only: If noise is permitted, the same values apply as for a mixing valve

Valves	Fittings set			
	Threaded connection			Welded connection
	Malleable cast iron	Brass ¹⁾		Steel
	Type / Item NO.	Type	Item NO.	Type / Item NO.
VVG44.15-0.25	ALG152	ALG152B	S55846-Z100	ALS202
VVG44.15-0.4				
VVG44.15-0.63				
VVG44.15-1				
VVG44.15-1.6				
VVG44.15-2.5				
VVG44.15-4				
VVG44.20-6.3	ALG202	ALG202B	S55846-Z102	ALS252
VVG44.25-10	ALG252	ALG252B	S55846-Z104	-
VVG44.32-16	ALG322	ALG322B	S55846-Z106	-
VVG44.40-25	ALG402	ALG402B	S55846-Z108	-
VXG44.15-0.25	ALG153	ALG153B	S55846-Z101	-
VXG44.15-0.4				
VXG44.15-0.63				
VXG44.15-1				
VXG44.15-1.6				
VXG44.15-2.5				
VXG44.15-4				
VXG44.20-6.3	ALG203	ALG203B	S55846-Z103	-
VXG44.25-10	ALG253	ALG253B	S55846-Z105	-
VXG44.32-16	ALG323	ALG323B	S55846-Z107	-
VXG44.40-25	ALG403	ALG403B	S55846-Z109	-

¹⁾ Medium temperature: Maximal 100 °C

$\Delta p_{\max}$ = Maximum permissible differential pressure over the valve control path, valid for the entire positioning range of the valve-actuator unit; if low noise operation is desired, we recommend a differential pressure of 200 kPa

Δp_s = Maximum permissible differential pressure (closing pressure) at which the valve-actuator unit securely closes against the pressure

Actuators: Overview

Typ3	Stock number	Operating voltage	Positioning		Spring return		Data sheet
			Signal	Time		Signal	
SAS31.00	S55158-A106	AC 230 V	3-position	120 s	-	-	N4581
SAS31.03	S55158-A107			30 s			
SAS31.50	S55158-A108			120 s	ja	< 28 s	
SAS31.53	S55158-A109			30 s	ja	< 14 s	
SAS61.03 ¹⁾	S55158-A100	AC/DC 24 V	DC 0...10 V DC 4...20 mA 0...1000 Ω	30 s	-	-	
SAS61.03U ²⁾	S55158-A100-A100						
SAS61.03/MO	S55158-A121						
SAS61.33 ¹⁾	S55158-A101		DC 0...10 V DC 4...20 mA 0...1000 Ω		ja	< 14 s	
SAS61.33U ²⁾	S55158-A101-A100						
SAS61.33U/MO	S55158-A122						
SAS61.53 ¹⁾	S55158-A102		DC 0...10 V DC 4...20 mA 0...1000 Ω				
SAS81.00 ¹⁾	S55158-A103	AC/DC 24 V	3-position	120 s	-	-	
SAS81.00U ²⁾	S55158-A103-A100						
SAS81.03 ¹⁾	S55158-A104			30 s			
SAS81.03U ²⁾	S55158-A104-A100			ja	< 14 s		
SAS81.33 ¹⁾	S55158-A105						
SAS81.33U ²⁾	S55158-A1105-A100						

¹⁾ Approbation CE+UL

²⁾ Approbation CE+UL, cable gland: ½" (UL514C)

Ordering

Please indicate material, article type, order text, and quantity; example:

Material	Article type	Order text	Quantity
VVG44.25-10	VVG44.25-10	Valve.	3
ALG252B	S55846-Z104	Fitting sets	3

Delivery

Valves, rotary actuators, and mounting kits are not assembled and are delivered in individual packaging and without a minimum order size.

Product documentation

Related documents such as environmental declarations, CE declarations, etc., can be downloaded at the following Internet address:

<http://siemens.com/bt/download>

Safety

	⚠ DANGER There is a risk to operating personnel and device when working on the unit Failure to comply with these safety notes can result in personal injury and damage to property from pipe pressure, electrical voltage, or device in operation. ☐ Note the following when servicing a valve/actuator: • Switch off both pump and operating voltage. • Close shutoff valves. • Release pressure in the pipes and allow them to cool down completely. • Disconnect electrical connections from the terminals as needed. • The actuator must be properly installed or manually adjusted prior to recommissioning the valve.
--	--

	⚠ CAUTION National safety regulations Failure to comply with national safety regulations may result in personal injury and property damage. • Observe national provisions and comply with the appropriate safety regulations.
--	--

Engineering

We recommend installing the valve with spring return since temperatures are lower on heating plants which increases the lifespan of the sealing gland on the stem.


A filter must be installed upstream of the valve to increase functional safety.

Mounting

It is easy to assemble the valve and actuator; it can be done at the construction site. No special tools or settings required.

Valve VVG44.. / VXG44.. is supplied with Mounting instructions M4364 (4 319 9564 0).

Mounting position




Pipe connection

Avoid leakage:

- Install fittings as per ISO 7-1.
- Do not use too much hemp or PTFE tape.
- Do not tighten pipe threading to "the very end".

Flow direction

Make sure that the valve is mounted in the proper flow direction. A symbol is applied to the valve body:

VVG44.. :			
Flow direction:			
VXG44.. :			
Mixing A / B to AB:		Diverting AB to A / B:	

Commissioning

The actuator must be properly mounted or manually adjusted before commissioning the valve.

VVG44..	
Turn the manual adjuster clockwise:	Valve opening = Increasing flow
Turn the manual adjuster counter clockwise:	Valve closing = Decreasing flow
VXG44..	
Turn the manual adjuster clockwise:	Through-put A – AB opens, bypass B closes
Turn the manual adjuster counter clockwise:	Through-put A – AB closes, bypass B opens

Maintenance

Valves VVG44.. and VXG44.. are maintenance free.

Stem sealing gland

The stem sealing gland cannot be exchanged. The entire valve must be replaced in the event of leakage. Contact your local Siemens office or branch for information.

Disposal

	⚠ WARNING
	Tensioned return spring Opening the valve housing can release the tensioned return spring resulting in flying parts that may cause injury. • Do not open the valve body.
	The valve is considered electrical and electronic equipment for disposal in terms of the applicable European Directive and may not be disposed of as domestic garbage. • Dispose of the valve through channels provided for this purpose. • Comply with all local and currently applicable laws and regulations.

Warranty

Technical data on specific applications are valid only together with Siemens products listed under "Equipment combinations". Siemens rejects any and all warranties in the event that third-party products are used.

Technical data

Functional data		
	VVG44..	VXG44..
PN class	PN 16 per ISO 7268	
Operating pressure	Per ISO 7005 within the permissible media temperature as per Section Technical design [→ 2]	
Characteristic curve 0...100 %	linear as per VDI / VDE 2173	
Leakage rate	0...0.02 % of k_{vs} value per DIN EN 1349	0...0.02 % of k_{vs} value per DIN EN 1349 (through-put and bypass)
Permissible media	Chilled water, hot water, water with frost temperature. Recommendation: Water treatment per VDI 2035	
Medium temperature ¹⁾	1...120 °C	
Rangeability S_v	DN 15: >50 or >100, see Section Type overview [→ 6] DN ≥20: >100	
Nominal stroke	5.5 mm	

Materials	
Housing	Bronze CC499K
Seat in through-put	CrNi steel, bronze (worked directly into housing) or Messing
Seat in bypass (VXG44.. only)	Bronze (worked directly into housing) or brass
Plug	CrNi steel or brass
Stem	CrNi steel
Sealing gland	Brass
Gland materials	EPDM-O rings


Dimensions / Weight	
See Dimensions [→ 14]	
Connections with external threading	G..B per ISO 228-1
Actuator fixing	G 3/4"

Standards, directives and approvals	
Pressure Equipment Directive	DGR 2014/68/EU
Pressure accessories	Range: Article 1, para. 1 Definition: Article 2, para. 5
Fluid group 2	Without CE certification as per article 3, para. 3 (generally applicable engineering practice) ²⁾
EAC compliance	Eurasian compliance
Environmental compatibility	Environmental Declaration CE1E4364en ³⁾ contains data on environmental-compatible product design and assessment (RoHS compliance, compositions, packaging, environmental benefits and disposal).

¹⁾ With ALG..B fitting up to 100 °C

²⁾ Fittings for a product where $PS \times DN < 1000$, do not require special testing and cannot have CE labeling

³⁾ See Section Product documentation [→ 10]



DN = Nominal size



H = Total height of actuator plus minimum mounting distance to wall or ceiling, for mounting, connection, operation, maintenance, etc.

H1 = Dimension from the pipe to the center to install actuator (upper edge)


H2 = Pipe center to the upper edge of the manual adjustment button, valve is in the "closed" position

Valve type	DN	B	G	L1	L2	L3	H1	H2	H	Weight	
		mm	Inch	mm	mm	mm	mm	mm	SAS..	kg	
VVG44.15-0.25	15	8,5	G 1B	100	50	58	45	55	>381	0.65	
VVG44.15-0.4											
VVG44.15-0.63											
VVG44.15-1											
VVG44.15-1.6							49	59			0.67
VVG44.15-2.5											
VVG44.15-4		12				53	63	0.77			
VVG44.20-6.3	20	9	G 1¼B	105	52.5	59	68	78	>396	1.0	
VVG44.25-10	25	11	G 1½B			62.5	71	81	>399	1.48	
VVG44.32-16	32		G 2B			63.5	77.5	87.5	>406	1.95	
VVG44.40-25	40		G 2¼B			76	80.5	90.5	>409	2.75	
VXG44.15-0.25	15	8.5	G 1B	100	50	50	45	55	>381	0.5	
VXG44.15-0.4											
VXG44.15-0.63											
VXG44.15-1											
VXG44.15-1.6							49	59			0.59
VXG44.15-2.5											
VXG44.15-4		53				63	0.67				
VXG44.20-6.3	20	9	G 1¼B	105	52.5	52.5	68	78	>396	0.90	
VXG44.25-10	25	11	G 1½B				71	81	>399	1.30	
VXG44.32-16	32		G 2B				77.5	87.5	>406	1.74	
VXG44.40-25	40		G 2¼B				80.5	90.5	>409	2.39	

Fittings

	Type	Article no.	Type	Article no.	For valve type	G	Rp
						[inch]	[inch]
VVG44.. 	ALG152	BPZ:ALG152	ALG152B	S55846-Z100	VVG44.15..	G 1	Rp ½
	ALG202	BPZ:ALG202	ALG202B	S55846-Z102	VVG44.20	G 1¼	Rp ¾
	ALG252	BPZ:ALG252	ALG252B	S55846-Z104	VVG44.25	G 1½	Rp 1
	ALG322	BPZ:ALG322	ALG322B	S55846-Z106	VVG44.32	G 2	Rp 1¼
	ALG402	BPZ:ALG402	ALG402B	S55846-Z108	VVG44.40	G 2¼	Rp 1½
VXG44.. 	ALG153	BPZ:ALG153	ALG153B	S55846-Z101	VXG44.15..	G 1	Rp ½
	ALG203	BPZ:ALG203	ALG203B	S55846-Z103	VXG44.20	G 1¼	Rp ¾
	ALG253	BPZ:ALG253	ALG253B	S55846-Z105	VXG44.25	G 1½	Rp 1
	ALG323	BPZ:ALG323	ALG323B	S55846-Z107	VXG44.32	G 2	Rp 1¼
	ALG403	BPZ:ALG403	ALG403B	S55846-Z109	VXG44.40	G 2¼	Rp 1½

- Valve side with cylindrical threading per ISO 228-1
- Pipe side with cylindrical threading per ISO 7-1
- ALG..B fittings up to 100 °C medium temperature

	Type	Article no.	For valve type	G	Rp
				[inch]	[inch]
	ALS202	BPZ:ALS202	VVG44.15..	G 1	26.8
	ALS252	BPZ:ALS252	VVG44.20	G 1¼	33.7
	-	-	VVG44.25	-	-
	-	-	VVG44.32	-	-
	-	-	VVG44.40	-	-

Replacement parts

Type	Item no.	Designation	Quantity
74 676 0273 0	74 676 0273 0	Rotary knob for small-stroke valves	10

Revision numbers

Type	Valid from rev. no.	Type	Valid from rev. no.
VVG44.. 2-port		VXG44.. 3-port	
VVG44.15-0.25	..01	VXG44.15-0.25	..01
VVG44.15-0.4	..01	VXG44.15-0.4	..01
VVG44.15-0.63	..01	VXG44.15-0.63	..01
VVG44.15-1	..01	VXG44.15-1	..01
VVG44.15-1.6	..01	VXG44.15-1.6	..01
VVG44.15-2.5	..01	VXG44.15-2.5	..01
VVG44.15-4	..01	VXG44.15-4	..01
VVG44.20-6.3	..01	VXG44.20-6.3	..01

Type	Valid from rev. no.	Type	Valid from rev. no.
VVG44.. 2-port		VXG44.. 3-port	
VVG44.25-10	..01	VXG44.25-10	..01
VVG44.32-16	..01	VXG44.32-16	..01
VVG44.40-25	..01	VXG44.40-25	..01